

University of New Hampshire

## University of New Hampshire Scholars' Repository

---

Division 10 – Specialties

Chapter 5 – Technical Construction and  
Renovation Standards

---

1-25-2013

### 101100 - Visual Display Surfaces

Stephanie L. Weatherbee

University of New Hampshire, [s.weatherbee@unh.edu](mailto:s.weatherbee@unh.edu)

Follow this and additional works at: [https://scholars.unh.edu/pdch\\_5\\_10](https://scholars.unh.edu/pdch_5_10)

---

#### Recommended Citation

Weatherbee, Stephanie L., "101100 - Visual Display Surfaces" (2013). *Division 10 – Specialties*. 1.  
[https://scholars.unh.edu/pdch\\_5\\_10/1](https://scholars.unh.edu/pdch_5_10/1)

This Article is brought to you for free and open access by the Chapter 5 – Technical Construction and Renovation Standards at University of New Hampshire Scholars' Repository. It has been accepted for inclusion in Division 10 – Specialties by an authorized administrator of University of New Hampshire Scholars' Repository. For more information, please contact [Scholarly.Communication@unh.edu](mailto:Scholarly.Communication@unh.edu).

## SECTION 10 1100 - VISUAL DISPLAY SURFACES

### 1.1 SUMMARY

#### A. Section Includes:

1. Chalkboards.
2. Markerboards.
3. Tackboards.
4. Sliding visual display units.
5. Visual display conference units.

### 1.2 SUBMITTALS

#### A. LEED Submittal:

1. Product Data for Credit EQ 4.4: For composite wood products, documentation indicating that the product contains no urea formaldehyde.

### 1.3 QUALITY ASSURANCE

A. Installer Qualifications: Manufacturer's authorized representative who is trained and approved for installation of motor-operated, sliding visual display units required for this Project.

B. Surface-Burning Characteristics: As determined by testing identical products according to ASTM E 84 by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.

1. Flame-Spread Index: 25 or less.
2. Smoke-Developed Index: 450 or less.

C. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.

### 1.4 CHALKBOARD ASSEMBLIES

A. Porcelain-Enamel Chalkboards: Balanced, high-pressure, factory-laminated chalkboard assembly of three-ply construction consisting of backing sheet, core material, and 0.021-inch- (0.53-mm-) thick, porcelain-enamel face sheet with matte finish.

#### 1. Manufacturers:

- a. Best-Rite Manufacturing.
- b. Claridge Products and Equipment, Inc.

- c. Marsh Industries, Inc.; Visual Products Group.
2. Particleboard Core: 3/8 inch (9.5 mm) thick; with 0.0129-inch- (0.35-mm-) thick, galvanized-steel sheet backing.
3. Laminating Adhesive: Manufacturer's standard, moisture-resistant thermoplastic type.

#### 1.5 MARKERBOARD ASSEMBLIES

- A. Porcelain-Enamel Markerboards: Balanced, high-pressure, factory-laminated markerboard assembly of three-ply construction consisting of backing sheet, core material, and 0.021-inch- (0.53-mm-) thick, porcelain-enamel face sheet with high-gloss finish.
  1. Manufacturers:
    - a. Best-Rite Manufacturing.
    - b. Claridge Products and Equipment, Inc.
    - c. Marsh Industries, Inc.; Visual Products Group.
  2. Particleboard Core: 1/2 inch (13 mm) thick; with 0.015-inch- (0.38-mm-) thick, aluminum sheet backing.

#### 1.6 TACKBOARD ASSEMBLIES

- A. Natural-Cork Tackboard: 1/4-inch- (6-mm-) thick, natural cork sheet factory laminated to 1/4-inch- (6-mm-) thick particleboard backing.

#### 1.7 SLIDING VISUAL DISPLAY UNITS

- A. Vertical-Sliding Visual Display Units: Factory-fabricated units consisting of extruded-aluminum tubular frame, fixed-rear visual display panel, and aluminum-framed vertical-sliding panels; designed for recessed mounting. Provide panels that operate smoothly without vibration or chatter.
  1. Manufacturers:
    - a. Claridge Products and Equipment, Inc.
  2. Type: Tubular frame on four sides. Unit shall be designed to support panels independent of wall.
  3. Two-Track Units: Fabricate unit with fixed rear panel covering entire rear surface. Provide two sliding panels, each equal to not less than one-half of overall height of unit.
  4. Sliding Panels: Fabricated from not less than 3/8-inch- (9.5-mm-) thick, kraft-paper honeycomb core; designed to be rigid and to resist warpage.

- a. Fabricate sliding panels with 0.021-inch (0.53-mm) uncoated thickness, porcelain-enamel face sheets.
5. Hardware: Manufacturer's standard, neoprene ball-bearing end rollers, four on each side of each sliding panel. Counterbalance each sliding panel with lead counterweights supported by steel aircraft cable over ball-bearing sheaves; with removable cover plate for access to counterweights. Provide rubber bumpers at top and bottom for each sliding panel.

#### 1.8 VISUAL DISPLAY WALL PANELS

- A. Product: 'Bulletin Board Linoleum,' as manufactured by FORBO Linoleum, Inc.
- B. Tack Wall Panels: With tackable surface.
  1. Linoleum Resilient Homogenous Material: 1/4-inch thick, linoleum resilient homogenous sheet, on jute backing, for direct application to wall surface.

#### 1.9 ACCESSORIES

- A. Field-Applied Wood Trim.
- B. Chalktray: Manufacturer's standard, continuous.
  1. Box Type: Extruded aluminum with slanted front, grooved tray, and cast-aluminum end closures.
- C. Map Rail: Satin anodized aluminum.
  1. Display Rail: Continuous and integral with map rail; fabricated from cork approximately 1 to 2 inches (25 to 50 mm) wide.
  2. End Stops: Located at each end of map rail.
  3. Map Hooks: Two map hooks for every 48 inches (1219 mm) of map rail or fraction thereof.

END OF SECTION 10 1100