

University of New Hampshire

## University of New Hampshire Scholars' Repository

---

Division 12 – Furnishings

Chapter 5 – Technical Construction and  
Renovation Standards

---

1-25-2013

### 122113 - Horizontal Louver Blinds

Stephanie L. Weatherbee

University of New Hampshire, Durham, s.weatherbee@unh.edu

Follow this and additional works at: [https://scholars.unh.edu/pdch\\_5\\_12](https://scholars.unh.edu/pdch_5_12)

---

#### Recommended Citation

Weatherbee, Stephanie L., "122113 - Horizontal Louver Blinds" (2013). *Division 12 – Furnishings*. 1.  
[https://scholars.unh.edu/pdch\\_5\\_12/1](https://scholars.unh.edu/pdch_5_12/1)

This Article is brought to you for free and open access by the Chapter 5 – Technical Construction and Renovation Standards at University of New Hampshire Scholars' Repository. It has been accepted for inclusion in Division 12 – Furnishings by an authorized administrator of University of New Hampshire Scholars' Repository. For more information, please contact [Scholarly.Communication@unh.edu](mailto:Scholarly.Communication@unh.edu).

## SECTION 12 2113 - HORIZONTAL LOUVER BLINDS

### 1.1 SUMMARY

#### A. Section Includes:

1. Horizontal louver blinds with aluminum slats.

#### B. General: All window treatments shall be approved by University Facilities Design and Construction prior to purchase.

### 1.2 SUBMITTALS

#### A. LEED Submittals:

1. Product Data for Credit MR 4.1 and Credit MR 4.2: For products having recycled content, documentation indicating percentages by weight of postconsumer and preconsumer recycled content. Include statement indicating costs for each product having recycled content.

### 1.3 HORIZONTAL LOUVER BLINDS, ALUMINUM SLATS

#### A. Manufacturers:

1. Hunter Douglas Contract.
2. Levolor Contract; a Newell Rubbermaid company.
3. Springs Window Fashions.

#### B. Slats: Aluminum; alloy and temper recommended by producer for type of use and finish indicated; with crowned profile and radius corners.

1. Width: 1 inch (25 mm).
2. Thickness: Not less than 0.008 inch (0.20 mm).
3. Finish: Ionized antistatic, dust-repellent, baked polyester finish.

#### C. Headrail: Formed steel or extruded aluminum; long edges returned or rolled. Headrails fully enclose operating mechanisms on three sides.

1. Capacity: One blind per headrail unless otherwise indicated.
2. Manual Lift Mechanism:
  - a. Lift-Cord Lock: Variable; stops lift cord at user-selected position within blind full operating range.
  - b. Operator: Extension of lift cord(s) through lift-cord lock mechanism to form cord pull.
3. Manual Tilt Mechanism: Enclosed worm-gear mechanism and linkage rod that adjusts ladders.

- D. Bottom Rail: Formed-steel or extruded-aluminum tube that secures and protects ends of ladders and lift cords and has plastic- or metal-capped ends.
- E. Lift Cords: Manufacturer's standard braided cord.
- F. Ladders: Evenly spaced across headrail at spacing that prevents long-term slat sag.
  - 1. Type: Braided cord.
- G. Valance: Two slats.

#### 1.4 HORIZONTAL LOUVER BLIND FABRICATION

- A. Product Safety Standard: Fabricate horizontal louver blinds to comply with WCMA A 100.1 including requirements for corded, flexible, looped devices; lead content of components; and warning labels.

#### 1.5 INSTALLATION

- A. Install horizontal louver blinds level and plumb, aligned and centered on openings, and aligned with adjacent units according to manufacturer's written instructions.
  - 1. Locate so exterior slat edges are not closer than 2 inches (51 mm) from interior faces of glass and not closer than 1-1/2 inches (38 mm) from interior faces of glazing frames through full operating ranges of blinds.
  - 2. Install mounting and intermediate brackets to prevent deflection of headrails.
  - 3. Install with clearances that prevent interference with adjacent blinds, adjacent construction, and operating hardware of glazed openings, other window treatments, and similar building components and furnishings.

END OF SECTION 12 2113